

AGRI-VATOR & ATTACHMENTS SPECIFICATIONS

AGRI-VATOR

AG 72

AG96

AG144

WEIGHT	1630 lbs	2045 lbs	2825 lbs
WORKING WIDTH		96"	144"
CENTER DRIVE GEARBOX	1:1.5 Tee	1:1.5 Tee	1:1.5 Tee
END DRIVE	3 Cx Belts (Left End)	2 Cx Belts (Both Ends)	3 Cx Belts (Both Ends)
TINE VIBRATION FREQUENCY	@ 540 PTO RPM = 1026 Cycles/Min	@ 540 PTO RPM = 1026 Cycles/Min	@ 540 PTO RPM = 1026 Cycles/Min
SIDE-TO-SIDE TINE TRAVEL	2 1/4 inches	2 1/4 inches	2 1/4 inches
VIBRATING DEPTH	6 inches	6 inches	6 inches
AERATION DENSITY	5 Holes per Sq. Ft	5 Holes per Sq. Ft	5 Holes per Sq. Ft
TINES	3/4 X 6" Forged And Hardened (144)	3/4 X 6" Forged And Hardened (192)	3/4 X 6" Forged And Hardened (288)
ROTOR BEARINGS	Double Sealed Tapered Roller	Double Sealed Tapered Roller	Double Sealed Tapered Roller
DRIVE LINE	1 3/8" Spline w/ Safety Shield	1 3/8" Spline w/ Safety Shield	1 3/8" Spline w/ Safety Shield
FINISH	Black Acrylic w Grey Trim	Black Acrylic w Grey Trim	Black Acrylic w Grey Trim

CLEATED ROLLER

WEIGHT	(Approx) 570 LBS	(Approx) 650 LBS	(Approx) 1075 LBS
DIAMETER	12"	12"	12"

SEEDER

WEIGHT	(Approx) 627 LBS	(Approx) 685 LBS	(Approx) 902 LBS
HOPPER CAPACITY	9 Bu	12 Bu	18 Bu
RATE CONTROL	Micro Flute Adjustment / Seed Cup	Micro Flute Adjustment / Seed Cup	Micro Flute Adjustment / Seed Cup
GAUGE MECHANISM	Interchangeable Sprockets	Interchangeable Sprockets	Interchangeable Sprockets
OUTLETS	12	16	24