

AERA-vator 80" Width & attachments

AERA-vator

Weight*
Working Width
Center Drive Gearbox
End Drive
Tine Vibration Frequency
Heavy Duty Lift/Trail Hitch
Drive Line
Finish
Roller Diameter
Rake Teeth Spacing
Tractor Requiement

*Add appropriate shaft weight (selected) to AERA-vator weight

80" Width

896 lbs
80"
1:1 Tee
3 "BX" 46 Belts (Each End)
@540 PTO RPM = 800 Cycles/Min
4 Ft. Turn Radius (approx.)
1 3/8" Spline w/ Safety Shield
Black Polyurethane w/ Grey Trim
8 5/8"
3 3/4" approx.
40-50 hp. Minimum lift capacity- 1700 lbs

AERA-vator Shaft

Shaft Weight*
Side-to-Side Tine Travel
Vibrating Depth
Aeration Density
Tines
Rotor Bearings

*Add shaft weight to AERA-vator

80" Width

320 lbs (requires 2 at 160 lbs)
1 3/8"
3 3/4"
9 Holes per sq ft (Approx.)
9/16" x 3 3/4" Forged and Hardened (192)
Double Sealed Tapered Roller

Multi-Tine Shaft

Shaft Weight*
Side-to-Side Tine Travel
Vibrating Depth
Aeration Density
Shells (6 per Rotor)
Rotor Bearings

*Add shaft weight to AERA-vator

80" Width

340 lbs (requires 2 at 170 lbs)
1/2"
up to 2" Deep
55 Holes per sq ft (approx.)
48
Double Sealed Tapered Roller

Slicer-Shaft

Shaft Weight*
Vibrating Depth
Aeration Density
Blade Spacing
Blades
Rotor Bearings
Vibration Blade Travel

80" Width

220 lbs (requires 2 at 110 lbs)
4 1/4 Inches Full Depth
6-7 Slits per sq ft (approx.)
5 inches
5" Long 10 Ga. Hardened Spring Steel (80ea)
50mm Ball Bearing
5/8" Vertical



AERA-vator 80" Width & attachments

Grooming/Rake Brush

Weight*

Swath

Rake Teeth Spacing

Brush Bristles

*Add shaft weight to AERA-vator when selected

80" Width

90 lbs

98 1/2 inches

1 7/8" (approx.)

4 1/2" Poly Bristle

Seeder

Weight*

Hopper Capacity

Rate Control

Gauge Mechanism

Outlets

*Add Seeder weight to AERA-vator weight (when selected)

80" Width

380 lbs

9.4 cubic ft

Micro Flute Adjustment/Seed Cup

Interchangeable Sprockets

20